

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

* 1 Identification

· **Product Identifier**

· **Trade Name: Precision Calibration Gas Mixture**

· **Product Number:** G-14315

· **Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

· **Product Description:**

Calibration gas mixture consisting of Toluene, Ethylbenzene, m-Xylene, p-Xylene, o-Xylene, Styrene, Undecane, Tetradecane and Nitrogen.

· **Details of the Supplier of the Safety Data Sheet:**

· **Manufacturer/Supplier:**

Gasco Affiliates, LLC
320 Scarlett Blvd.
Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

· **Emergency telephone number:**

Inside the US: 1-833-723-3267 (Chemtrec, 24 hours)

Outside the US: 1-703-527-3887 (Chemtrec, 24 hours)

2 Hazard(s) Identification

· **Classification of the substance or mixture:**



Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

· **Label elements:**

· **Hazard pictograms:**



· **Signal word:** Warning

· **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

· **Precautionary statements:**


P410+P403 Protect from sunlight. Store in a well-ventilated place.

· **Unknown acute toxicity:**

100 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 0

Reactivity = 0

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

· HMIS-ratings (scale 0 - 4)

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:

CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ⚠ Press. Gas, H280; Simple Asphyxiant	99.9992-99.999992%
CAS: 108-88-3 RTECS: XS 5250000	Toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	0.000001-0.0001%
CAS: 100-41-4 RTECS: DA 0700000	Ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	0.000001-0.0001%
CAS: 108-38-3 RTECS: ZE 2275000	m-xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0.000001-0.0001%
CAS: 106-42-3 RTECS: ZE 2625000	p-xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0.000001-0.0001%
CAS: 95-47-6 RTECS: ZE 2450000	o-xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0.000001-0.0001%
CAS: 100-42-5 RTECS: WL 3675000	Styrene ⚠ Flam. Liq. 3, H226; ⚠ Carc. 2, H351; Repr. 2, H361; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	0.000001-0.0001%
CAS: 1120-21-4 RTECS: YQ 1525000	Undecane ⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	0.000001-0.0001%
CAS: 629-59-4	Tetradecane ⚠ Asp. Tox. 1, H304; Flam. Liq. 4, H227	0.000001-0.0001%

4 First-Aid Measures

· Description of first aid measures

· After inhalation:

Generally the product does not irritate with inhalation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in the side position for transportation.

· After skin contact:

Generally, the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

Wash with soap and water.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

If skin irritation occurs, consult a doctor.

· **After eye contact:**

Not anticipated under normal use.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Not a normal route of entry.

If swallowed and symptoms occur, consult a doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

* 5 Fire-Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information.

· **Special hazards arising from the substance or mixture:**

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Carbon and Nitrogen (NOx).

· **Advice for firefighters**

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

· **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:**

Treat any fumes as toxic.

Ensure adequate ventilation.

Keep people at a distance and stay upwind.

In a confined area, NIOSH approved respiratory protection may be required.

· **Environmental precautions:** Inform authorities in case of gas release.

· **Methods and material for containment and cleaning up:**

Dispose of the collected material according to regulations.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· **Handling**

· **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

· **Information about protection against explosions and fires:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

· **Conditions for safe storage, including any incompatibilities** Store away from strong oxidizing agents.

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· **Components with occupational exposure limits:**

7727-37-9 Nitrogen

TLV | withdrawn TLV, see App. F; simple asphyxiant

108-88-3 Toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

100-41-4 Ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

108-38-3 m-xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

106-42-3 p-xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
95-47-6 o-xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
100-42-5 Styrene	
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m ³ , 100 ppm Long-term value: 215 mg/m ³ , 50 ppm
TLV	Short-term value: 170 mg/m ³ , 40 ppm Long-term value: 85 mg/m ³ , 20 ppm BEI

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

· **Breathing equipment:**

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· **Protection of hands:** Not required.

· **Eye protection:** Not necessary under normal conditions.

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Gaseous

Color: Clear, colorless

Odor: Odorless

Odor threshold: Not determined.

pH-value: Not determined.

· **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: Not determined.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Flash point:** None
- **Flammability (solid, gaseous):** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
 - Relative density:** Not determined.
 - Vapor density:** Not determined.
 - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Carbon Oxides and Nitrogen Oxides (NOx).

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

108-88-3 Toluene		
Oral	LD50	5000 mg/kg (Rat)
Dermal	LD50	12124 mg/kg (Rabbit)
Inhalative	LC50/4 h	12.5-28.8 mg/l (Rat)
100-41-4 Ethylbenzene		
Oral	LD50	3500 mg/kg (Rat)
Dermal	LD50	15433 mg/kg (Rabbit)
108-38-3 m-xylene		
Oral	LD50	5000 mg/kg (Rat)

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

Dermal	LD50	14100 mg/kg (Rabbit)
106-42-3 p-xylene		
Oral	LD50	5000 mg/kg (Rat)
100-42-5 Styrene		
Oral	LD50	2650 mg/kg (Rat)
Inhalative	LC50/4 h	12 mg/l (Rat)

- **Primary irritant effect:**

- **On the skin:** No irritating effect.

- **On the eye:** No irritating effect.

- **Additional toxicological information:**

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

- Group 1 - Carcinogenic to humans

- Group 2A - Probably carcinogenic to humans

- Group 2B - Possibly carcinogenic to humans

- Group 3 - Not classifiable as to its carcinogenicity to humans

- Group 4 - Probably not carcinogenic to humans

108-88-3	Toluene	3
100-41-4	Ethylbenzene	2B
108-38-3	m-xylene	3
106-42-3	p-xylene	3
95-47-6	o-xylene	3
100-42-5	Styrene	2B

- **NTP (National Toxicology Program):**

- 100-42-5 Styrene

R

- **OSHA-Ca (Occupational Safety & Health Administration):**

- None of the ingredients are listed.

12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:**

- 108-88-3 Toluene**

- EC50 10 mg/l (Green algae)

- 8.0 mg/l (Water flea)

- 100-41-4 Ethylbenzene**

- EC50 4.9 mg/l (Green algae)

- 1.8-2.4 mg/l (Water flea)

- 100-42-5 Styrene**

- EC50 4.7 mg/l (Water flea)

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Generally not hazardous for water.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup. GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:** The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packaging**
- **Recommendation:** Return cylinder and unused product to supplier.

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT** Compressed gas, n.o.s.
- **ADR/ADN** UN1956 Compressed gas, n.o.s.
- **IMDG, IATA** COMPRESSED GAS, N.O.S.
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.2
- **Label:** 2.2

· **ADR/ADN**

- **Class:** 2.2 1A
- **Label:** 2.2

· **IMDG, IATA**

- **Class:** 2.2
- **Label:** 2.2
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Special precautions for user:** Not applicable.
- **Hazard identification number (Kemler code):** 20
- **EMS Number:** F-C,S-V
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

- **ADR/ADN**
- **Excepted quantities (EQ):** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1956 COMPRESSED GAS, N.O.S., 2.2, (E)

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

108-88-3	Toluene
100-41-4	Ethylbenzene
108-38-3	m-xylene
106-42-3	p-xylene
95-47-6	o-xylene
100-42-5	Styrene

- **TSCA (Toxic Substances Control Act):**

7727-37-9	Nitrogen
108-88-3	Toluene
100-41-4	Ethylbenzene
108-38-3	m-xylene
106-42-3	p-xylene
95-47-6	o-xylene
100-42-5	Styrene
1120-21-4	Undecane
629-59-4	Tetradecane

- **California Proposition 65:**

- **Chemicals known to cause cancer:**

100-41-4	Ethylbenzene
----------	--------------

- **Chemicals known to cause reproductive toxicity for females:**

108-88-3	Toluene
----------	---------

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture**Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

Carcinogenic categories:**EPA (Environmental Protection Agency):**

108-88-3	Toluene	II
100-41-4	Ethylbenzene	D
108-38-3	m-xylene	I
106-42-3	p-xylene	I
95-47-6	o-xylene	I

TLV (Threshold Limit Value established by ACGIH):

108-88-3	Toluene	A4
100-41-4	Ethylbenzene	A3
108-38-3	m-xylene	A4
106-42-3	p-xylene	A4
95-47-6	o-xylene	A4
100-42-5	Styrene	A4

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:**Signal word:** Warning**Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary statements:

P410+P403 Protect from sunlight. Store in a well-ventilated place.

National regulations:

None of the ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other Information****Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

Date of last revision/ revision number: 06/21/2020 / -**Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Press. Gas: Gases under pressure – Compressed gas
Press. Gas: Gases under pressure – Dissolved gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106