

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

### 1 Identification

- **Product Identifier**
- **Trade Name: Precision Calibration Gas Mixture**
- **Product Number:** G-15615
- **Relevant identified uses of the substance or mixture and uses advised against:**  
Used for calibration of gas measuring devices. Not suitable for human consumption.
- **Product Description:** Calibration gas mixture consisting of Propylene Oxide and Nitrogen.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
Gasco Affiliates, LLC  
320 Scarlett Blvd.  
Oldsmar, FL 34677
- TELEPHONE NUMBER: (800) 910-0051  
FAX NUMBER: (866) 755-8920  
E-MAIL: info@gascogas.com
- **Emergency telephone number:**  
Inside the US: 1-833-723-3267 (Chemtrec, 24 hours)  
Outside the US: 1-703-527-3887 (Chemtrec, 24 hours)

### \* 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Gas cylinder

Press. Gas      H280 Contains gas under pressure; may explode if heated.



Health hazard

Muta. 1B      H340 May cause genetic defects.

Carc. 1B      H350 May cause cancer.

Simple Asphyxiant      May displace oxygen and cause rapid suffocation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**  
Propylene Oxide
- **Hazard statements:**  
H280 Contains gas under pressure; may explode if heated.  
H340 May cause genetic defects.  
H350 May cause cancer.  
May displace oxygen and cause rapid suffocation.
- **Precautionary statements:**  
P201 Obtain special instructions before use.

(Contd. on page 2)

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

## Trade Name: Precision Calibration Gas Mixture

- P202 Do not handle until all safety precautions have been read and understood.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P405 Store locked up.  
 P410+P403 Protect from sunlight. Store in a well-ventilated place.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

99.9 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMS-ratings (scale 0 - 4)**

HEALTH	*0	Health = *0
FIRE	0	Fire = 0
REACTIVITY	0	Physical Hazard = 0

· **Hazard(s) not otherwise classified (HNOC):** None known

### 3 Composition/Information on Ingredients

· **Chemical characterization: Substance**

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 75-56-9 RTECS: TZ 2975000	Propylene Oxide 	0.0002-0.1%
CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen 	99.9-99.9998%

### 4 First-Aid Measures

· **Description of first aid measures**

· **After inhalation:**

Generally the product does not irritate with inhalation.  
 Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.  
 In case of unconsciousness place patient stably in the side position for transportation.

· **After skin contact:**

Generally, the product does not irritate the skin.  
 In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.  
 Wash with soap and water.  
 If skin irritation occurs, consult a doctor.

· **After eye contact:**

Not anticipated under normal use.  
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Not a normal route of entry.  
 If swallowed and symptoms occur, consult a doctor.

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

### Trade Name: Precision Calibration Gas Mixture

- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

### 5 Fire-Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
Use fire fighting measures that suit the environment.  
Use water spray to cool fire-exposed containers.
- **For safety reasons unsuitable extinguishing agents:** No further relevant information.
- **Special hazards arising from the substance or mixture:**  
Closed containers may explode when exposed to extreme heat.  
If incinerated, product will release the following toxic fumes: Oxides of Carbon and Nitrogen (NOx).
- **Advice for firefighters**  
This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire. Firefighters should be aware of the presence of Hydrogen Sulfide in this gas mixture, which can cause significant health effects.
- **Special protective equipment for firefighters:**  
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
Treat any fumes as toxic.  
Ensure adequate ventilation.  
Keep people at a distance and stay upwind.  
In a confined area, NIOSH approved respiratory protection may be required.
- **Environmental precautions:** Inform authorities in case of gas release.
- **Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Dispose of the collected material according to regulations.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.
- **Information about protection against explosions and fires:**  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not cut, grind or weld on container that contains or contained product.  
Do not spray on a naked flame or any incandescent material.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

### Trade Name: Precision Calibration Gas Mixture

- **Conditions for safe storage, including any incompatibilities** Store away from strong oxidizing agents.
- **Storage**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s):** No further relevant information available.

### 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**  
All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

#### · **Components with occupational exposure limits:**

##### **7727-37-9 Nitrogen**

TLV	withdrawn TLV, see App. F; simple asphyxiant
-----	--

##### **75-56-9 Propylene Oxide**

PEL	Long-term value: 240 mg/m <sup>3</sup> , 100 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 4.8 mg/m <sup>3</sup> , 2 ppm
	DSEN

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing and wash before reuse.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.  
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:** Not required.
- **Material of gloves:** Not required.
- **Penetration time of glove material:** Not applicable.
- **Eye protection:** Not required.
- **Body protection:** Not required.

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

**Trade Name: Precision Calibration Gas Mixture**

### 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - Form:** Gaseous
  - Color:** Clear, colorless
- **Odor:** Odorless
- **Odor threshold:** Not determined.
- **pH-value:** Not available  
Not determined.
- **Change in condition**
  - Melting point/Melting range:** Not determined.
  - Boiling point/Boiling range:** Not determined.
- **Flash point:** None
- **Flammability (solid, gaseous):** Not determined.
- **Ignition temperature:** Not applicable
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
  - Relative density:** Not determined.
  - Vapor density:** Not determined.
  - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Other information:** No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Carbon Oxides, Nitrogen Oxides (NO<sub>x</sub>) and Sulfur Oxides.

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

**Trade Name: Precision Calibration Gas Mixture**

### 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 75-56-9 Propylene Oxide

Oral	LD50	380 mg/kg (Rat)
Dermal	LD50	1245 mg/kg (Rabbit)

- **Primary irritant effect:**

- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Carcinogenic

The product can cause inheritable damage.

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

75-56-9	Propylene Oxide	2B
---------	-----------------	----

- **NTP (National Toxicology Program):**

75-56-9	Propylene Oxide	R
---------	-----------------	---

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

### 12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment:**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

**Trade Name: Precision Calibration Gas Mixture**

### 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**  
Observe all federal, state and local environmental regulations when disposing of this material.  
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG).  
Remove or cover any hazard labels. Return empty cylinder for recycling.  
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup.  
GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:** The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packaging**
- **Recommendation:** Return cylinder and unused product to supplier.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT, IATA** Compressed gas, n.o.s.
- **ADR/ADN** UN1956 Compressed gas, n.o.s.
- **IMDG** COMPRESSED GAS, N.O.S.
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.2
- **Label:** 2.2

#### · ADR/ADN



- **Class:** 2.2 1A
- **Label:** 2.2

#### · IMDG, IATA



- **Class:** 2.2
- **Label:** 2.2
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Hazard identification number (Kemler code):** 20
- **EMS Number:** F-C,S-V

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

### Trade Name: Precision Calibration Gas Mixture

· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations:</b>	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
<hr/>	
· <b>ADR/ADN</b>	
· <b>Excepted quantities (EQ):</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ):</b>	120 ml
· <b>Excepted quantities (EQ):</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1956 COMPRESSED GAS, N.O.S., 2.2

### \* 15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

#### · **Section 355 (extremely hazardous substances):**

75-56-9	Propylene Oxide
---------	-----------------

#### · **Section 313 (Specific toxic chemical listings):**

75-56-9	Propylene Oxide
---------	-----------------

#### · **TSCA (Toxic Substances Control Act):**

7727-37-9	Nitrogen
-----------	----------

75-56-9	Propylene Oxide
---------	-----------------

#### · **California Proposition 65:**

#### · **Chemicals known to cause cancer:**

75-56-9	Propylene Oxide
---------	-----------------

#### · **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

#### · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

#### · **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

#### · **Carcinogenic categories:**

#### · **EPA (Environmental Protection Agency):**

75-56-9	Propylene Oxide	B2
---------	-----------------	----

#### · **TLV (Threshold Limit Value established by ACGIH):**

75-56-9	Propylene Oxide	A3
---------	-----------------	----

#### · **NIOSH-Ca (National Institute for Occupational Safety and Health):**

75-56-9	Propylene Oxide
---------	-----------------

(Contd. on page 9)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

### Trade Name: Precision Calibration Gas Mixture

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



- **Signal word:** Danger

- **Hazard-determining components of labeling:**

Propylene Oxide

- **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

H340 May cause genetic defects.

H350 May cause cancer.

May displace oxygen and cause rapid suffocation.

- **Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

None of the ingredients are listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other Information

- **Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

- **Date of last revision/ revision number:** 08/08/2020 / -

- **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 10)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 08/08/2020

Reviewed on 08/08/2020

### Trade Name: Precision Calibration Gas Mixture

REL: Recommended Exposure Limit  
Press. Gas: Gases under pressure – Compressed gas  
Press. Gas: Gases under pressure – Dissolved gas  
Flam. Liq. 1: Flammable liquids – Category 1  
Acute Tox. 4: Acute toxicity – Category 4  
Acute Tox. 3: Acute toxicity – Category 3  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Muta. 1B: Germ cell mutagenicity – Category 1B  
Carc. 1B: Carcinogenicity – Category 1B  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106