

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

* 1 Identification

· **Product Identifier**

· **Trade Name: Precision Calibration Gas Mixture G-24919**

· **Product Number:** G-24919

· **Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

· **Product Description:** Calibration gas mixture consisting of Oxygen and Nitrogen.

· **Details of the Supplier of the Safety Data Sheet:**

· **Manufacturer/Supplier:**

Gasco Affiliates, LLC

320 Scarlett Blvd.

Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

· **Emergency telephone number:**

Inside the US: 1-833-723-3267 (Chemtrec, 24 hours)

Outside the US: 1-703-527-3887 (Chemtrec, 24 hours)

2 Hazard(s) Identification

· **Classification of the substance or mixture:**



Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

· **Label elements:**

· **Hazard pictograms:**



· **Signal word:** Warning

· **Hazard-determining components of labeling:**

Hexane

· **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

H361 Suspected of damaging fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

· **Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

- P405 Store locked up.
 P410+P403 Protect from sunlight. Store in a well-ventilated place.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

This value refers to knowledge of known, established toxicological or ecotoxicological values.
 99 % of the mixture consists of component(s) of unknown toxicity.

- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
 · **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	*0	Health = *0
FIRE	0	Fire = 0
REACTIVITY	0	Physical Hazard = 0

- **Hazard(s) not otherwise classified (HNOC):** None known

3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
 · **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen Press. Gas, H280; Simple Asphyxiant	99-99.9995%
CAS: 110-54-3 RTECS: MN 9275000	Hexane Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0.0005-1%

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· **Description of first aid measures**

· **After inhalation:**

Generally the product does not irritate with inhalation.
 Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
 In case of unconsciousness place patient stably in the side position for transportation.

· **After skin contact:**

Generally, the product does not irritate the skin.
 If skin irritation occurs, consult a doctor.
 In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

· **After eye contact:**

Not anticipated under normal use.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Not a normal route of entry.
 If swallowed and symptoms occur, consult a doctor.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

5 Fire-Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Use fire fighting measures that suit the environment.
Use water spray to cool fire-exposed containers.
- **For safety reasons unsuitable extinguishing agents:** No further relevant information.
- **Special hazards arising from the substance or mixture:**
Closed containers may explode when exposed to extreme heat.
If incinerated, product will release the following toxic fumes: Oxides of Nitrogen (NOx) and Carbon.
- **Advice for firefighters**
This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.
- **Special protective equipment for firefighters:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:** Ensure adequate ventilation.
- **Environmental precautions:** Inform authorities in case of gas release.
- **Methods and material for containment and cleaning up:**
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7727-37-9	Nitrogen	7.96E+05 ppm
110-54-3	Hexane	260 ppm

· PAC-2:

7727-37-9	Nitrogen	8.32E+05 ppm
110-54-3	Hexane	2900* ppm

· PAC-3:

7727-37-9	Nitrogen	8.69E+05 ppm
110-54-3	Hexane	8600** ppm

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

Do not cut, grind or weld on container that contains or contained product.
Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities** Store away from strong oxidizing agents.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

7727-37-9 Nitrogen

TLV | withdrawn TLV, see App. F; simple asphyxiant

110-54-3 Hexane

PEL | Long-term value: 1800 mg/m³, 500 ppm

REL | Long-term value: 180 mg/m³, 50 ppm

TLV | Long-term value: 176 mg/m³, 50 ppm
Skin; BEI

- **Ingredients with biological limit values:**

110-54-3 Hexane

BEI | 0.4 mg/L
urine
end of shift at end of workweek
2.5-Hexanedione without hydrolysis

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment**

- **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

- **Breathing equipment:** Not required.

- **Protection of hands:** Not required.

- **Material of gloves:** Not applicable.

- **Penetration time of glove material:** Not applicable.

- **Eye protection:** Not required.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** Compressed gas
 - **Color:** Clear, colorless
- **Odor:** Odorless
- **Odor threshold:** Not determined.
- **pH-value:** Not applicable.
- **Change in condition**
 - **Melting point/Melting range:** Not determined.
 - **Boiling point/Boiling range:** Not determined.
- **Flash point:** None
- **Flammability (solid, gaseous):** Not determined.
- **Ignition temperature:** Not applicable
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
 - **Lower:** Not determined.
 - **Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
 - **Relative density:** Not determined.
 - **Vapor density:** Not determined.
 - **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - **Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Solvent content:**
 - **Organic solvents:** 1.0 %
 - **VOC content:** 1.00 %
 - **Solids content:** 0.0 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** Stable under normal conditions.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Nitrogen Oxides (NOx) and Carbon Oxides.

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

110-54-3 Hexane

Oral	LD50	25,000 mg/kg (Rat)
Inhalative	LC50/4 h	48,000 mg/l (Rat) 1 hour

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.
- **Additional toxicological information:**
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
 - Group 1 - Carcinogenic to humans
 - Group 2A - Probably carcinogenic to humans
 - Group 2B - Possibly carcinogenic to humans
 - Group 3 - Not classifiable as to its carcinogenicity to humans
 - Group 4 - Probably not carcinogenic to humans

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:**

110-54-3 Hexane

EC50	12,840 mg/l (Green algae)
	3,878 mg/l (Water flea) (48 hr)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup. GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:** The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packaging**
- **Recommendation:** Return cylinder and unused product to supplier.

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT** Compressed gas, n.o.s.
- **ADR/ADN** UN1956 COMPRESSED GAS, N.O.S.
- **IMDG, IATA** COMPRESSED GAS, N.O.S.
- **Transport hazard class(es):**

- **DOT**



- **Class:** 2.2
- **Label:** 2.2

- **ADR/ADN**



- **Class:** 2 1A Gases

- **IMDG, IATA**



- **Class:** 2.2
- **Label:** 2.2
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Warning: Gases
- **Hazard identification number (Kemler code):** 20
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919**· Transport/Additional information:****· ADR/ADN****· Excepted quantities (EQ):**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1956 COMPRESSED GAS, N.O.S., 2.2

15 Regulatory Information**· Safety, health and environmental regulations/legislation specific for the substance or mixture:****· SARA (Superfund Amendments and Reauthorization):****· Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

110-54-3 Hexane

· TSCA (Toxic Substances Control Act):

7727-37-9 Nitrogen

110-54-3 Hexane

· California Proposition 65:**· Chemicals known to cause cancer:**

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

110-54-3 Hexane

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· New Jersey Right-to-Know List:

All ingredients are listed.

· New Jersey Special Hazardous Substance List:

110-54-3 Hexane

F3

· Pennsylvania Right-to-Know List:

All ingredients are listed.

· Pennsylvania Special Hazardous Substance List:

None of the ingredients are listed.

· Carcinogenic categories:**· EPA (Environmental Protection Agency):**

110-54-3 Hexane

II

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919**Hazard pictograms:****Signal word:** Warning**Hazard-determining components of labeling:**

Hexane

Hazard statements:

H280 Contains gas under pressure; may explode if heated.

H361 Suspected of damaging fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

None of the ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other Information****Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

Date of last revision/ revision number: 07/18/2020 / -**Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Press. Gas: Gases under pressure – Compressed gas

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/18/2020

Reviewed on 07/18/2020

Trade Name: Precision Calibration Gas Mixture G-24919

Press. Gas: Gases under pressure – Dissolved gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106