

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

* 1 Identification

- **Product Identifier**
- **Trade Name: Precision Calibration Gas Mixture**
- **Product Number:** G-34417
- **Relevant identified uses of the substance or mixture and uses advised against:**
Used for calibration of gas measuring devices. Not suitable for human consumption.
- **Product Description:** Calibration gas mixture consisting of Sulfur Dioxide, Carbon Dioxide and Nitrogen.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Gasco Affiliates, LLC
320 Scarlett Blvd.
Oldsmar, FL 34677

- TELEPHONE NUMBER: (800) 910-0051
FAX NUMBER: (866) 755-8920
E-MAIL: info@gascogas.com
- **Emergency telephone number:**
Inside the US: 1-833-723-3267 (Chemtrec, 24 hours)
Outside the US: 1-703-527-3887 (Chemtrec, 24 hours)

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Gas cylinder


Press. Gas H280 Contains gas under pressure; may explode if heated.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Warning
- **Hazard statements:**
H280 Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.
- **Precautionary statements:**
P410+P403 Protect from sunlight. Store in a well-ventilated place.
- **Unknown acute toxicity:**
This value refers to knowledge of known, established toxicological or ecotoxicological values.
100 % of the mixture consists of component(s) of unknown toxicity.
- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- **NFPA ratings (scale 0 - 4)**

Health = 0
Fire = 0
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

· HMIS-ratings (scale 0 - 4)

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:

CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ⚠ Press. Gas, H280; Simple Asphyxiant	74.9995-99.8995%
CAS: 124-38-9 RTECS: FF 6400000	Carbon Dioxide ⚠ Press. Gas, H280; Simple Asphyxiant	0.1-25%
CAS: 7446-09-5	Sulfur Dioxide ⚠ Press. Gas, H280; ⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314	0.0005-0.0999%

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· Description of first aid measures

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in the side position for transportation.

· After skin contact:

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.
Wash with soap and water.
If skin irritation occurs, consult a doctor.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Not a normal route of entry.
If swallowed and symptoms occur, consult a doctor.

· Information for doctor

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

5 Fire-Fighting Measures

· Extinguishing media

· Suitable extinguishing agents:

Use fire fighting measures that suit the environment.
Use water spray to cool fire-exposed containers.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information is available.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

- **Special hazards arising from the substance or mixture:**

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Carbon, Nitrogen (NO_x) and Sulfur.

- **Advice for firefighters**

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

- **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**

Treat any fumes as toxic.

Keep away from ignition sources

Ensure adequate ventilation.

Keep people at a distance and stay upwind.

In a confined area, NIOSH approved respiratory protection may be required.

- **Environmental precautions:** Inform authorities in case of gas release.

- **Methods and material for containment and cleaning up:**

Dispose concrete tiles as solid waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

7727-37-9	Nitrogen	7.96E+05 ppm
7446-09-5	Sulfur Dioxide	0.20 ppm

- **PAC-2:**

7727-37-9	Nitrogen	8.32E+05 ppm
7446-09-5	Sulfur Dioxide	0.75 ppm

- **PAC-3:**

7727-37-9	Nitrogen	8.69E+05 ppm
7446-09-5	Sulfur Dioxide	30 ppm

7 Handling and Storage

- **Handling**

- **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

- **Information about protection against explosions and fires:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not cut, grind or weld on container that contains or contained product.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities**

Store away from strong oxidizing agents, strong reducing agents, phosphorous, organic materials, powdered metals and Zinc.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituents have no known exposure limits.

7727-37-9 Nitrogen	
TLV	withdrawn TLV, see App. F; simple asphyxiant
124-38-9 Carbon Dioxide	
PEL	Long-term value: 9000 mg/m ³ , 5000 ppm
REL	Short-term value: 54,000 mg/m ³ , 30,000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm
TLV	Short-term value: 54,000 mg/m ³ , 30,000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment**

- **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

- **Protection of hands:** Not required.

- **Material of gloves:** Not applicable.

- **Penetration time of glove material:** Not applicable.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

· **Eye protection:**



Tightly sealed goggles

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Gaseous
Color:	Clear, colorless
Odor:	Rotten
Odor threshold:	Not determined.

· **pH-value:** Not available

· **Change in condition**

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.

· **Flash point:** None

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:** Not applicable

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not self-igniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure:** Not determined.

· **Density:**

Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not applicable.

· **Solubility in / Miscibility with:**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:**

VOC content: 0.00 %

Solids content: 0.0 %

· **Other information:** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**
Strong oxidizing agents, strong reducing agents, phosphorous, organic materials, powdered metals and Zinc.
- **Hazardous decomposition products:** Carbon Oxides, Nitrogen Oxides (NOx) and Sulfur Dioxide.

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

7446-09-5 Sulfur Dioxide

Inhalative	LC50/4 h	1,260 mg/l (Rat)
------------	----------	------------------

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.
- **Additional toxicological information:**
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

7446-09-5	Sulfur Dioxide	3
-----------	----------------	---

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

- **Toxicity:** The hazards for the aquatic environment are unknown.
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**
Observe all federal, state and local environmental regulations when disposing of this material.
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG).
Remove or cover any hazard labels. Return empty cylinder for recycling.
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup.
GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:** The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packaging**
- **Recommendation:** Return cylinder and unused product to supplier.

14 Transport Information

- **UN-Number:** UN1956
- **DOT, ADR/ADN, IMDG, IATA** UN1956
- **UN proper shipping name:** Compressed gas, n.o.s.
- **DOT** UN1956 Compressed gas, n.o.s.
- **ADR/ADN** COMPRESSED GAS, N.O.S.
- **IMDG, IATA**
- **Transport hazard class(es):**

- **DOT**



- **Class:** 2.2
- **Label:** 2.2

- **ADR/ADN**



- **Class:** 2.2 1A
- **Label:** 2.2

- **IMDG, IATA**



- **Class:** 2.2
- **Label:** 2.2
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Hazard identification number (Kemler code):** 20
- **EMS Number:** F-C,S-V

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations:	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

· ADR/ADN	
· Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG	
· Limited quantities (LQ):	120 ml
· Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1956 COMPRESSED GAS, N.O.S., 2.2

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

7446-09-5 Sulfur Dioxide

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

7727-37-9 Nitrogen

124-38-9 Carbon Dioxide

7446-09-5 Sulfur Dioxide

· **California Proposition 65:**· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **New Jersey Right-to-Know List:**

All ingredients are listed.

· **New Jersey Special Hazardous Substance List:**

None of the ingredients are listed.

· **Pennsylvania Right-to-Know List:**

All ingredients are listed.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

· Pennsylvania Special Hazardous Substance List:		
7446-09-5	Sulfur Dioxide	E

· **Carcinogenic categories:**

· EPA (Environmental Protection Agency):		
None of the ingredients are listed.		

· **TLV (Threshold Limit Value established by ACGIH):**

7446-09-5	Sulfur Dioxide	A4
-----------	----------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.		
-------------------------------------	--	--

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



· **Signal word:** Warning

· **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

· **Precautionary statements:**

P410+P403 Protect from sunlight. Store in a well-ventilated place.

· **National regulations:**

None of the ingredients are listed.		
-------------------------------------	--	--

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

· **Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

· **Date of last revision/ revision number:** 07/03/2020 / -

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 07/03/2020

Reviewed on 07/03/2020

Trade Name: Precision Calibration Gas Mixture

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Press. Gas: Gases under pressure – Compressed gas

Press. Gas: Gases under pressure – Dissolved gas

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106