

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

* 1 Identification

· **Product Identifier**

· **Trade Name: Precision Calibration Gas Mixture**

· **Product Number:** G-9215

· **Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

· **Product Description:**

Calibration gas mixture consisting of Carbon Dioxide, Methane, Ethane, Propane, n-Butane, Isobutane, n-Pentane, Isopentane and Nitrogen.

· **Details of the Supplier of the Safety Data Sheet:**

· **Manufacturer/Supplier:**

Gasco Affiliates, LLC
320 Scarlett Blvd.
Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

· **Emergency telephone number:**

Inside the US: 1-833-723-3267 (Chemtrec, 24 hours)

Outside the US: 1-703-527-3887 (Chemtrec, 24 hours)

2 Hazard(s) Identification

· **Classification of the substance or mixture:**



Flame

Flam. Gas 1 H220 Extremely flammable gas.



Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

· **Label elements:**

· **Hazard pictograms:**



· **Signal word:** Danger

· **Hazard statements:**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

· **Precautionary statements:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Unknown acute toxicity:**
98.3 % of the mixture consists of component(s) of unknown toxicity.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	4	Fire = 4
REACTIVITY	0	Physical Hazard = 0

- **Hazard(s) not otherwise classified (HNOC):** None known

3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous Components:

CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ⚠ Press. Gas, H280; Simple Asphyxiant	44.9-58.3%
CAS: 124-38-9 RTECS: FF 6400000	Carbon Dioxide ⚠ Press. Gas, H280; Simple Asphyxiant	0.2-1.2%
CAS: 109-66-0 RTECS: RZ 9450000	Pentane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	0.1-0.3%
CAS: 78-78-4 RTECS: EK 4430000	Isopentane ⚠ Flam. Liq. 1, H224; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	0.1-0.3%
CAS: 74-82-8 RTECS: PA 1490000	Methane ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280; Simple Asphyxiant	0.8-8.2%
CAS: 74-84-0 RTECS: KH 3800000	Ethane ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280; ⚠ Skin Irrit. 2, H315; ⚠ STOT SE 3, H335; Eye Irrit. 2B, H320	0.2-2%
CAS: 74-98-6 RTECS: TX 2275000	Propane ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280	0.1-0.4%
CAS: 106-97-8 RTECS: EJ 4200000	butane ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280	0.1-0.4%
CAS: 75-28-5 RTECS: TZ 4300000	Isobutane ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280	0.1-0.3%

4 First-Aid Measures

- **Description of first aid measures**
- **After inhalation:**
Generally the product does not irritate with inhalation.
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in the side position for transportation.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **After skin contact:**

Generally, the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

Wash with soap and water.

If skin irritation occurs, consult a doctor.

- **After eye contact:**

Not anticipated under normal use.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Not a normal route of entry.

If swallowed and symptoms occur, consult a doctor.

- **Information for doctor**

- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

* 5 Fire-Fighting Measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

- **For safety reasons unsuitable extinguishing agents:** No further relevant information.

- **Special hazards arising from the substance or mixture:**

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Carbon and Nitrogen (NOx).

- **Advice for firefighters**

Certain variations of this gas mixture are flammable. Containers, when involved in fire, may rupture or burst in the heat of the fire.

- **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**

Treat any fumes as toxic.

Keep away from ignition sources

Ensure adequate ventilation.

Keep people at a distance and stay upwind.

Wear protective equipment. Keep unprotected persons away.

In a confined area, NIOSH approved respiratory protection may be required.

- **Environmental precautions:** Inform authorities in case of gas release.

- **Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

7 Handling and Storage

- **Handling**

- **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

- **Information about protection against explosions and fires:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

Store away from strong oxidizing agents, phosphorous, organic materials and powdered metals.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

74-82-8 Methane	
TLV	refer to Appendix F in TLVs and BEIs book
7727-37-9 Nitrogen	
TLV	withdrawn TLV, see App. F; simple asphyxiant
74-84-0 Ethane	
TLV	Refer to Appendix F in TLVs and BEIs book
124-38-9 Carbon Dioxide	
PEL	Long-term value: 9000 mg/m ³ , 5000 ppm
REL	Short-term value: 54,000 mg/m ³ , 30,000 ppm
	Long-term value: 9000 mg/m ³ , 5000 ppm

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

TLV	Short-term value: 54,000 mg/m ³ , 30,000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm
74-98-6 Propane	
PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs and BEIs book
106-97-8 butane	
REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: 2370 mg/m ³ , 1000 ppm
75-28-5 Isobutane	
TLV	Short-term value: 2370 mg/m ³ , 1000 ppm
109-66-0 Pentane	
PEL	Long-term value: 2950 mg/m ³ , 1000 ppm
REL	Long-term value: 350 mg/m ³ , 120 ppm Ceiling limit value: 1800* mg/m ³ , 610* ppm *15-min
TLV	Long-term value: 2950 mg/m ³ , 1000 ppm
78-78-4 Isopentane	
PEL	Long-term value: 2950 mg/m ³ , 1000 ppm
TLV	Long-term value: 2950 mg/m ³ , 1000 ppm

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· **Protection of hands:** Not required.

· **Eye protection:** Not necessary under normal conditions.

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Gaseous

Color:

Clear, colorless

· **Odor:**

Odorless

· **Odor threshold:**

Not determined.

· **pH-value:**

Not available

· **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

Not determined.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Flash point:** None
- **Flammability (solid, gaseous):** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
 - Relative density:** Not determined.
 - Vapor density:** Not determined.
 - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Heat, flame and ignition sources.
- **Incompatible materials:** Strong oxidizing agents, phosphorous, organic materials and powdered metals.
- **Hazardous decomposition products:** Carbon Oxides and Nitrogen Oxides (NOx).

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
109-66-0 Pentane		
Oral	LD50	5000 mg/kg (Mouse)
Dermal	LD50	3000 mg/kg (Rabbit)
Inhalative	LC50/4 h	364 mg/l (Rat)
74-82-8 Methane		
Inhalative	LC50/4 h	217 mg/l (Mouse)
106-97-8 butane		
Inhalative	LC50/4 h	658 mg/l (Rat)

Oral	LD50	5000 mg/kg (Mouse)
Dermal	LD50	3000 mg/kg (Rabbit)
Inhalative	LC50/4 h	364 mg/l (Rat)

Inhalative	LC50/4 h	217 mg/l (Mouse)
------------	----------	------------------

Inhalative	LC50/4 h	658 mg/l (Rat)
------------	----------	----------------

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.
- **Additional toxicological information:**
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
 - Group 1 - Carcinogenic to humans
 - Group 2A - Probably carcinogenic to humans
 - Group 2B - Possibly carcinogenic to humans
 - Group 3 - Not classifiable as to its carcinogenicity to humans
 - Group 4 - Probably not carcinogenic to humans

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:**

109-66-0 Pentane

EC50 9.74 mg/l (Water flea)

78-78-4 Isopentane

EC50 2.3 mg/l (Water flea)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

- **Waste treatment methods**

- **Recommendation:**

Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG).

Remove or cover any hazard labels. Return empty cylinder for recycling.

NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup.

GASCO encourages the consumer to return all cylinders.

- **Waste disposal key:** The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packaging**
- **Recommendation:** Return cylinder and unused product to supplier.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture**14 Transport Information**

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1954
- **UN proper shipping name:**
- **DOT** Compressed gas, flammable, n.o.s.
- **ADR/ADN** UN1954 Compressed gas, flammable, n.o.s.
- **IMDG, IATA** COMPRESSED GAS, FLAMMABLE, N.O.S.
- **Transport hazard class(es):**

· **DOT**

- **Class:** 2.1
- **Label:** 2.1

· **ADR/ADN**

- **Class:** 2.1 1F
- **Label:** 2.1

· **IMDG, IATA**

- **Class:** 2.1
- **Label:** 2.1
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Hazard identification number (Kemler code):** 23
- **EMS Number:** F-D,S-U
- **Stowage Category** D
- **Stowage Code** SW2 Clear of living quarters.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: Forbidden
On cargo aircraft only: 150 kg

· **ADR/ADN**

- **Excepted quantities (EQ):** Code: E0
Not permitted as Excepted Quantity

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **IMDG**
- **Limited quantities (LQ):** 0
- **Excepted quantities (EQ):** Code: E0
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1954 COMPRESSED GAS, FLAMMABLE, N.O.S., 2.1

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

74-82-8 Methane

7727-37-9 Nitrogen

7782-44-7 Oxygen

74-84-0 Ethane

124-38-9 Carbon Dioxide

74-98-6 Propane

106-97-8 butane

75-28-5 Isobutane

109-66-0 Pentane

78-78-4 Isopentane

· **California Proposition 65:**· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories:**· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture**Hazard pictograms:****Signal word:** Danger**Hazard statements:**

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- May displace oxygen and cause rapid suffocation.

Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
- P381 Eliminate all ignition sources if safe to do so.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.

National regulations:

None of the ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other Information****Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

Date of last revision/ revision number: 06/21/2020 / -**Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety and Health
 OSHA: Occupational Safety & Health Administration
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Gas 1: Flammable gases – Category 1
 Press. Gas: Gases under pressure – Compressed gas
 Press. Gas: Gases under pressure – Dissolved gas
 Flam. Liq. 1: Flammable liquids – Category 1
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106