

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

* 1 Identification

Product Identifier**Trade Name: Precision Calibration Gas Mixture****Product Number:** G-9315**Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

Product Description:

Calibration gas mixture consisting of Carbon Monoxide, Hydrogen Sulfide, Sulfur Dioxide, Pentane, Oxygen and Nitrogen.

Details of the Supplier of the Safety Data Sheet:**Manufacturer/Supplier:**Gasco Affiliates, LLC
320 Scarlett Blvd.
Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

Emergency telephone number:

Inside the US: 1-833-723-3267 (Chemtrec, 24 hours)

Outside the US: 1-703-527-3887 (Chemtrec, 24 hours)

2 Hazard(s) Identification

Classification of the substance or mixture:

Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



Acute Tox. 4 H332 Harmful if inhaled.

Label elements:**Hazard pictograms:****Signal word:** Warning**Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

Unknown acute toxicity:

99.2 % of the mixture consists of component(s) of unknown toxicity.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
REACTIVITY	0	Physical Hazard = 0

- **Hazard(s) not otherwise classified (HNOC):** None known

3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous Components:

CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ⚠ Press. Gas, H280; Simple Asphyxiant	78.234-81.648%
CAS: 109-66-0 RTECS: RZ 9450000	Pentane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	0.35-0.75%
CAS: 630-08-0 RTECS: FG 3500000	Carbon Monoxide ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280; ⚠ Acute Tox. 3, H331; ⚠ Repr. 1A, H360; STOT RE 1, H372	0.001-0.01%
CAS: 7783-06-4	Hydrogen Sulfide ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280; ⚠ Acute Tox. 2, H330; ⚠ Aquatic Acute 1, H400	0.0005-0.005%
CAS: 7782-44-7	Oxygen ⚠ Oxid. Gas 1, H270; ⚠ Press. Gas, H280	18-21%
CAS: 7446-09-5	Sulfur Dioxide ⚠ Press. Gas, H280; ⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314	0.0005-0.001%

4 First-Aid Measures

Description of first aid measures

General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Generally, the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

Wash with soap and water.

If skin irritation occurs, consult a doctor.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **After eye contact:**
Not anticipated under normal use.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Not a normal route of entry.
If swallowed and symptoms occur, consult a doctor.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

* 5 Fire-Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Use fire fighting measures that suit the environment.
Use water spray to cool fire-exposed containers.
- **For safety reasons unsuitable extinguishing agents:** No further relevant information.
- **Special hazards arising from the substance or mixture:**
Closed containers may explode when exposed to extreme heat.
If incinerated, product will release the following toxic fumes: Oxides of Carbon, Nitrogen (NOx) and Sulfur.
- **Advice for firefighters**
This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire. Firefighters should be aware of the presence of Hydrogen Sulfide in this gas mixture, which can cause significant health effects.
- **Special protective equipment for firefighters:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**
Treat any fumes as toxic.
Ensure adequate ventilation.
Keep people at a distance and stay upwind.
In a confined area, NIOSH approved respiratory protection may be required.
- **Environmental precautions:** Inform authorities in case of gas release.
- **Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not cut, grind or weld on container that contains or contained product.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities**

Store away from strong oxidizing agents, strong bases, phosphorous, organic materials and powdered metals, Alkali metals, Alkaline Earth metals, Alkali metal oxides, Zinc.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

7727-37-9 Nitrogen

TLV | withdrawn TLV, see App. F; simple asphyxiant

630-08-0 Carbon Monoxide

PEL	Long-term value: 55 mg/m ³ , 50 ppm
REL	Long-term value: 40 mg/m ³ , 35 ppm Ceiling limit value: 229 mg/m ³ , 200 ppm
TLV	Long-term value: 29 mg/m ³ , 25 ppm BEI

7783-06-4 Hydrogen Sulfide

PEL	Ceiling limit value: 20; 50* ppm *10-min peak; once per 8-hr shift
REL	Ceiling limit value: 15* mg/m ³ , 10* ppm *10-min
TLV	Short-term value: 7 mg/m ³ , 5 ppm Long-term value: 1.4 mg/m ³ , 1 ppm

109-66-0 Pentane

PEL	Long-term value: 2950 mg/m ³ , 1000 ppm
REL	Long-term value: 350 mg/m ³ , 120 ppm Ceiling limit value: 1800* mg/m ³ , 610* ppm *15-min
TLV	Long-term value: 2950 mg/m ³ , 1000 ppm

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Exposure controls:**
- **Personal protective equipment**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
- **Breathing equipment:**



Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

- **Material of gloves:**

The selection of the suitable gloves depends on the material, and marks of quality, and varies from manufacturer to manufacturer.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:**



Protective work clothing

9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - **Form:** Gaseous
 - **Color:** Clear, colorless
- **Odor:** Rotten
- **Odor threshold:** Not determined.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **pH-value:** Not available
- **Change in condition**
 - Melting point/Melting range:** Not determined.
 - Boiling point/Boiling range:** Not determined.
- **Flash point:** None
- **Flammability (solid, gaseous):** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
 - Relative density:** Not determined.
 - Vapor density:** Not determined.
 - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**
Strong oxidizing agents, strong bases, phosphorous, organic materials and powdered metals, Alkali metals, Alkaline Earth metals, Alkali metal oxides, Zinc.
- **Hazardous decomposition products:** Carbon Oxides, Nitrogen Oxides (NO_x) and Sulfur Oxides.

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

109-66-0 Pentane

Oral	LD50	5000 mg/kg (Mouse)
Dermal	LD50	3000 mg/kg (Rabbit)
Inhalative	LC50/4 h	364 mg/l (Rat)

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

7783-06-4 Hydrogen Sulfide		
Inhalative	LC50/4 h	634 mg/l (Mouse) 444 mg/l (Rat)
	LC50/96 hours	0.016 mg/l (Pimephales)
630-08-0 Carbon Monoxide		
Inhalative	LC50/4 h	7520 mg/l (Rat)
7446-09-5 Sulfur Dioxide		
Inhalative	LC50/4 h	5040 mg/l (Rat)

- **Primary irritant effect:**
- **On the skin:** No irritating effect.
- **On the eye:** No irritating effect.
- **Additional toxicological information:**
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
 - Group 1 - Carcinogenic to humans
 - Group 2A - Probably carcinogenic to humans
 - Group 2B - Possibly carcinogenic to humans
 - Group 3 - Not classifiable as to its carcinogenicity to humans
 - Group 4 - Probably not carcinogenic to humans

7446-09-5	Sulfur Dioxide	3
-----------	----------------	---

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:**

109-66-0 Pentane

EC50 | 9.74 mg/l (Water flea)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

- **Waste treatment methods**

- **Recommendation:**

Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.

NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup.

GASCO encourages the consumer to return all cylinders.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **Waste disposal key:** The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packaging**
- **Recommendation:** Return cylinder and unused product to supplier.

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT** Compressed gas, n.o.s.
- **ADR/ADN** UN1956 Compressed gas, n.o.s.
- **IMDG, IATA** COMPRESSED GAS, N.O.S.
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.2
- **Label:** 2.2

· **ADR/ADN**

- **Class:** 2.2 1A
- **Label:** 2.2

· **IMDG, IATA**

- **Class:** 2.2
- **Label:** 2.2
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Hazard identification number (Kemler code):** 20
- **EMS Number:** F-C,S-V
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations:** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

- **ADR/ADN**

- **Excepted quantities (EQ):**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- **IMDG**

- **Limited quantities (LQ):**

120 ml

- **Excepted quantities (EQ):**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":**

UN 1956 COMPRESSED GAS, N.O.S., 2.2

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- **SARA (Superfund Amendments and Reauthorization):**

- **Section 355 (extremely hazardous substances):**

7783-06-4 Hydrogen Sulfide

7446-09-5 Sulfur Dioxide

- **Section 313 (Specific toxic chemical listings):**

7783-06-4 Hydrogen Sulfide

- **TSCA (Toxic Substances Control Act):**

7727-37-9 Nitrogen

7782-44-7 Oxygen

109-66-0 Pentane

630-08-0 Carbon Monoxide

7783-06-4 Hydrogen Sulfide

7446-09-5 Sulfur Dioxide

- **California Proposition 65:**

- **Chemicals known to cause cancer:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

- **Carcinogenic categories:**

- **EPA (Environmental Protection Agency):**

7783-06-4 Hydrogen Sulfide

I

- **TLV (Threshold Limit Value established by ACGIH):**

7446-09-5 Sulfur Dioxide

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

· **Hazard pictograms:**



· **Signal word:** Warning

· **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

· **Precautionary statements:**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

· **National regulations:**

None of the ingredients are listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

· **Relevant phrases:**

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

· **Date of last revision/ revision number:** 06/21/2020 / -

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety and Health
 OSHA: Occupational Safety & Health Administration
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Gas 1: Flammable gases – Category 1
 Oxid. Gas 1: Oxidizing gases – Category 1
 Press. Gas: Gases under pressure – Compressed gas
 Press. Gas: Gases under pressure – Dissolved gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Acute Tox. 2: Acute toxicity – Category 2
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 06/21/2020

Reviewed on 06/21/2020

Trade Name: Precision Calibration Gas Mixture

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106